

EUROLAN Fiber patchcord MPO-MPO

Multimode OM4



Ordering information

Part number	Description
49L-40-12-FA-xx*	MPO -MPO multimode 12F OM4, Female type A
49L-40-24-FA-xx*	MPO -MPO multimode 24F OM4, Female type A

Ordering information

Part number	Description
49L-40-12-FB-xx*	MPO -MPO multimode 12F OM4, Female type B
49L-40-24-FB-xx*	MPO -MPO multimode 24F OM4, Female type B

* Available in lengths 2,3,5,7,10,15,20,25 meters

Application

- CATV and Multimedia
- Telecommunication Networks
- Active Device Termination
- Gigabit Ethernet
- Interconnection for O/E Modules
- Data Processing Networks
- Optical Switch Interframe Connection
- Premise Installations
- Asynchronous Transmission Mode(ATM)

Optical termination

Type	Multimode (PC/Flat polish) Package
Performance	Elite Low Loss
Maximum Insertion Loss	≤0,35dB
Return Loss	≥30dB
Operating Temperature	-40°C to +80°C
Test Wavelength	850nm or 1300nm
Durability (500 times)	≤0,1dB
Tensile strength	>15kg

- ✓ High temperature stability
- ✓ Good exchangeability
- ✓ Good durability
- ✓ Low insertion loss
- ✓ High back reflection loss
- ✓ Standard:
Telcordia GR-1435-CORE compliant
EIC 61754-7 and
TIA 604-5-D